Outlook 2.0

September 9, 2024



Outlook September 9, 2024

Contents

Outlook	2
Folders	2
Mails	3

Outlook

This documents the Outlook module and how to use it from JavaScript flows.

You can load the module using the following code:

```
1 var outlook = Module.load("Outlook", {version: "2.0.4"});
```

Folders

The Outlook module has a folders property that contains a list of all the folders in the user's mailbox. Each folder has the following properties:

- name: The name of the folder
- mails: A list of all the mails in the folder

The special folder Inbox is also available as a property on the folders object and on the module itself.

```
1 var inbox = outlook.inbox;
2 // also
3 var sameInbox = outlook.folders.inbox;
```

Create a new folder

Create a new top-level folder. The folder will be created in the root of the mailbox.

It might not be possible to create a top-level folder. This depends on the user's mailbox configuration.

```
1 var newFolder = outlook.createFolder("My new folder");
```

You can also create a subfolder of an existing folder:

```
1 // newFolder is the folder created in the example above
2 var newSubFolder = newFolder.createFolder("My new folder");
```

Outlook September 9, 2024

Mails

Each mail has the following properties:

- subject: The subject of the mail
- body: The body of the mail
- from: The sender of the mail
- to: The recipients of the mail
- cc: The CC recipients of the mail
- bcc: The BCC recipients of the mail
- attachments: A list of attachments
- received: The received datetime of the mail
- sent: The sent datetime of the mail
- read: Whether the mail has been read (get and set)
- important: Whether the mail is marked as important (get and set)
- flagged: Whether the mail is flagged (get and set)

A mail object also has the following methods:

- reply(info): Reply to the mail with the given info object should contain a body property at least
- replyAll(info): Reply to all recipients of the mail with the given info object should contain a body property at least
- forward(info): Forward the mail with the given info object should contain a body property at least
- move(folder): Move the mail to the given folder (must be a folder object)
- delete(): Delete the mail

Sending a mail

To send a new mail, use the send method on the module:

```
const outlook = Module.load("Outlook", {version: "2.0.4"});
outlook.send({
    to: "john@doe.org",
    subject: "Hello",
    body: "Hello John!"
});
```

You can use the following properties in the mail object:

• to: The recipient of the mail

Outlook September 9, 2024

- cc: The CC recipient of the mail
- bcc: The BCC recipient of the mail
- subject: The subject of the mail
- body: The body of the mail
- attachments: A list of paths to files to attach

Attachments

Each attachment has the following properties:

- name: The name of the attachment
- path: The path to the attachment on disk
- size: The size of the attachment in bytes